

# PROFESSIONAL AIR TOOLS IN TAIWAN


*Herramientas  
Neumáticas en Taiwan*

台灣專業製造 氣動工具



**ALTA-PRO**

-台灣艾普牌氣動工具-



| PROFESSIONAL | HIGH QUALITY |

[www.alta-pro.com.tw](http://www.alta-pro.com.tw)

## JS-MRP-1337

### MEDIUM PRESSURE AIR SPRAY GUN

- Optional Nozzle:  
\*1.3, 1.4, 1.7mm
- Cup Capacity:  
600 c.c Gravity Nylon Cup
- Gun Weight : 457g
- Air Inlet : 1/4" PS
- Fluid inlet : M16 X 1.5P



| Item No.<br>型號              | JS-MRP-1337<br>Reduced Pressure |
|-----------------------------|---------------------------------|
| Type                        | LVMP中壓                          |
| Fluid Output<br>出漆量 (l/Min) | 265                             |
| Pattern Width<br>噴幅 (m/m)   | 320                             |
| Air Cons.<br>耗氣量 (l/Min.)   | 360                             |
| Air Pressure<br>使用壓力 (PSI)  | 15~35                           |

## JS-MRP-1758

### MEDIUM PRESSURE AIR SPRAY GUN

- Optional Nozzle:  
1.2, 1.3mm
- Cup Capacity:  
600 c.c Gravity Nylon Cup
- Gun Weight : 510g
- Air Inlet : 1/4" PS
- Fluid Inlet : 3/8" PF



| Item No.<br>型號              | JS-MRP-1758<br>Reduced Pressure |
|-----------------------------|---------------------------------|
| Type                        | LVMP中壓                          |
| Fluid Output<br>出漆量 (l/Min) | 235                             |
| Pattern Width<br>噴幅 (m/m)   | 300                             |
| Air Cons.<br>耗氣量 (l/Min.)   | 300                             |
| Air Pressure<br>使用壓力 (PSI)  | 15~28                           |

## JS-MRP-1718

### MEDIUM PRESSURE AIR SPRAY GUN

- Optional Nozzle:  
1.3, \*1.4, 1.7, 1.9, 2.1, 2.5mm
- Cup Capacity:  
600 c.c Gravity Nylon Cup
- Gun Weight : 448g
- Air Inlet : 1/4" PS
- Fluid Inlet : M16 X 1.5P
- Packing : 10 PCs/ Ctn /  
N.W. : 10kgs / G.W. : 11kgs / 2.0'



| Item No.<br>型號              | JS-MRP-1718<br>Reduced Pressure |
|-----------------------------|---------------------------------|
| Type                        | LVMP中壓                          |
| Fluid Output<br>出漆量 (l/Min) | 220                             |
| Pattern Width<br>噴幅 (m/m)   | 290                             |
| Air Cons.<br>耗氣量 (l/Min.)   | 280                             |
| Air Pressure<br>使用壓力 (PSI)  | 18~35                           |

## JS-MRP-1618

### MEDIUM PRESSURE AIR SPRAY GUN

- Optional Nozzle:  
1.3, \*1.4, 1.7, 1.9, 2.1, 2.5mm
- Cup Capacity:  
600 c.c Gravity Nylon Cup
- Gun Weight : 448g
- Air Inlet : 1/4" PS
- Fluid Inlet : M16 X 1.5P
- Packing : 10 PCs/ Ctn /  
N.W. : 10kgs / G.W. : 11kgs / 2.0'



| Item No.<br>型號              | JS-MRP-1618<br>Reduced Pressure |
|-----------------------------|---------------------------------|
| Type                        | LVMP中壓                          |
| Fluid Output<br>出漆量 (l/Min) | 220                             |
| Pattern Width<br>噴幅 (m/m)   | 290                             |
| Air Cons.<br>耗氣量 (l/Min.)   | 280                             |
| Air Pressure<br>使用壓力 (PSI)  | 18~35                           |

## JS-MH 1005

### HVLP AIR SPRAY GUN

- Optional Nozzle :  
1.0, 1.2, 1.3, \*1.4, 1.5, 1.6, 1.8, 2.0, 2.5mm
- Cup Capacity :  
600 c.c Gravity Nylon Cup
- Gun Weight : 514g
- Air Inlet : 1/4" PF
- Fluid Inlet : M16 X 1.5P
- Packing : 10 Pcs/ Ctn /  
N.W. : 10kgs/ G.W.:11kgs/ 1.7'



| Item No.<br>型號              | JS-MH 1005 |
|-----------------------------|------------|
| Type                        | HVLP環保型    |
| Fluid Output<br>出漆量 (l/Min) | 150        |
| Pattern Width<br>噴幅 (m/m)   | 310        |
| Air Cons.<br>耗氣量 (l/Min.)   | 270        |
| Air Pressure<br>使用壓力 (PSI)  | 15~28      |

## JS-M-1314 JS-MH-1314

- Optional Nozzle :  
1.2, 1.3, \*1.4, 1.6, 1.8, 2.0, 2.5mm
- Cup Capacity :  
600 C.C Gravity Nylon Cup
- Gun Weight : 448 g
- Air Inlet : 1/4" PF
- Fluid Inlet : M16 X 1.5 P
- Package : 10 Pcs / Ctn / N.W. :  
10Kgs/ G..W.:11 Kgs/ 1.7'



| Item No.<br>型號              | JS-M 1314 | JS-MH 1314 |
|-----------------------------|-----------|------------|
| Type                        | HP 高壓     | HVLP 環保型   |
| Fluid Output<br>出漆量 (l/Min) | 220       | 150        |
| Pattern Width<br>噴幅 (m/m)   | 310       | 310        |
| Air Cons.<br>耗氣量 (l/Min.)   | 210       | 270        |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28      |

## JS-G-1325

- Optional Nozzle :  
0.8, 1.1, 1.3, \*1.4,  
1.5, 1.8, 2.0, 2.5 mm
- Cup Capacity :  
400 C.C Gravity Cup
- Gun Weight : 440 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 10 Pcs / Ctn / N.W. :  
11Kgs/ G..W.:12 Kgs/ 1.7'



| Item No.<br>型號              | JS-G1325 |
|-----------------------------|----------|
| Type                        | HP 高壓    |
| Fluid Output<br>出漆量 (l/Min) | 190      |
| Pattern Width<br>噴幅 (m/m)   | 260      |
| Air Cons.<br>耗氣量 (l/Min.)   | 190      |
| Air Pressure<br>使用壓力 (PSI)  | 30~45    |

## JS-S-1325

- Optional Nozzle :  
0.8, 1.1, 1.3, 1.4, 1.5,  
\*1.8, 2.0, 2.5 mm
- Cup Capacity :  
700 C.C or 1000C.C Suction Cup
- Gun Weight : 440 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 3/8" or 1/4" NPS
- Package : 10 Pcs / Ctn / N.W. :  
13Kgs/ G..W.:14 Kgs/ 1.7'



| Item No.<br>型號              | JS-S1325 |
|-----------------------------|----------|
| Type                        | HP 高壓    |
| Fluid Output<br>出漆量 (l/Min) | 190      |
| Pattern Width<br>噴幅 (m/m)   | 265      |
| Air Cons.<br>耗氣量 (l/Min.)   | 200      |
| Air Pressure<br>使用壓力 (PSI)  | 30~45    |



## JS-S-1201

- Optional Nozzle:  
1.3, \*1.5, 1.8, 2.0, 2.5
- Cup capacity:  
700c.c or 1000c.c
- Gun weight 355g
- Air Inlet: 1/4PF
- Fluid inlet: 1/4"NPS or 3/8"PS



| Item No.<br>型號              | JS-S 1201 |
|-----------------------------|-----------|
| Type                        | HP高壓      |
| Fluid Output<br>出漆量 (l/Min) | 190       |
| Pattern Width<br>噴幅 (m/m)   | 280       |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     |

## JS-S-1202

- Optional Nozzle:  
\*1.5, 1.8, 2.0, 2.5
- Cup capacity:  
700c.c or 1000c.c
- Gun weight 430g
- Air Inlet: 1/4PS
- Fluid inlet: 1/4"NPS or 3/8"PS



| Item No.<br>型號              | JS-S 1202 |
|-----------------------------|-----------|
| Type                        | HP高壓      |
| Fluid Output<br>出漆量 (l/Min) | 360       |
| Pattern Width<br>噴幅 (m/m)   | 330       |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       |
| Air Pressure<br>使用壓力 (PSI)  | 15~43     |

## JS-M-1114

## JS-MH-1114

## JS-ML-1114

- Optional Nozzle :  
1.0, 1.2, 1.3, \*1.4, 1.5, 1.6, 1.8, 2.0, 2.5mm
- Cup Capacity :  
600 C.C Gravity Nylon Cup
- Gun Weight : 514 g
- Air Inlet : 1/4" PF
- Fluid Inlet : M16 X 1.5 P
- Package : 10 Pcs / Ctn / N.W. : 10Kgs/ G.W.: 11 Kgs/ 1.7'



| Item No.<br>型號              | JS-M 1114 | JS-MH 1114 | JS-ML 1114 |
|-----------------------------|-----------|------------|------------|
| Type                        | HP高壓      | HVLP環保型    | LVL P 環保優型 |
| Fluid Output<br>出漆量 (l/Min) | 220       | 150        | 140        |
| Pattern Width<br>噴幅 (m/m)   | 310       | 310        | 310        |
| Air Cons.<br>耗氣量 (l/Min.)   | 210       | 270        | 270        |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28      | 15~28      |

## Mini Spray Gun

## JS-MH-1753

- Optional Nozzle:  
0.5, 0.8, 1.0, 1.2mm
- Cup capacity:  
125 c.c Gravity Nylon Cup
- Gun weight 308g
- Air Inlet: 1/4"PF
- Fluid inlet: M14\*1.0P



| Item No.<br>型號              | JS-MH-1753 |
|-----------------------------|------------|
| Type                        | HVLP環保型    |
| Fluid Output<br>出漆量 (l/Min) | 86         |
| Pattern Width<br>噴幅 (m/m)   | 180        |
| Air Cons.<br>耗氣量 (l/Min.)   | 130        |
| Air Pressure<br>使用壓力 (PSI)  | 15~28      |

### JS-MH-1768

- Optional Nozzle :  
1.3, \*1.4, 1.5, 1.7,  
2.0, 2.5 mm
- Cup Capacity :  
600 C.C Gravity Nylon Cup
- Gun Weight : 620 g
- Air Inlet : 1/4" PF
- Fluid Inlet : M16 X 1.5 P
- Package : 10 Pcs / Ctn / N.W. :  
10Kgs/ G..W.:11 Kgs/ 1.7'



| Item No.<br>型號              | JS-MH 1768 |
|-----------------------------|------------|
| Type                        | HVLP 環保型   |
| Fluid Output<br>出漆量 (l/Min) | 140        |
| Pattern Width<br>噴幅 (m/m)   | 300        |
| Air Cons.<br>耗氣量 (l/Min.)   | 260        |
| Air Pressure<br>使用壓力 (PSI)  | 15~28      |

### JS-M-1566 JS-MH-1788

- Optional Nozzle :  
1.0, 1.3,\*1.4, 1.5, 1.7,  
2.0, 2.5, 3.0,3.5mm
- Cup Capacity :  
600 C.C Gravity Nylon Cup
- Gun Weight : 620 g
- Air Inlet : 1/4" PF
- Fluid Inlet : M16 X 1.5 P
- Package : 10 Pcs / Ctn / N.W. :  
10Kgs/ G..W.:11 Kgs/ 1.7'



| Item No.<br>型號              | JS-M 1566 | JS-MH 1788 |
|-----------------------------|-----------|------------|
| Type                        | HP 高壓     | HVLP 環保型   |
| Fluid Output<br>出漆量 (l/Min) | 220       | 140        |
| Pattern Width<br>噴幅 (m/m)   | 260       | 300        |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       | 260        |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28      |

### JS-M-1008 JS-MH-1008

- Optional Nozzle :  
1.0, 1.3,\*1.4, 1.5, 1.7,  
2.0, 2.5, 3.0, 3.5mm
- Cup Capacity : 600 C.C Gravity Nylon Cup
- Gun Weight : 620 g
- Air Inlet : 1/4" PF
- Fluid Inlet : M16 X 1.5 P
- Package : 10 Pcs / Ctn / N.W. :  
11Kgs/ G..W.:12 Kgs/ 1.7'



| Item No.<br>型號              | JS-M 1008 | JS-MH 1008 |
|-----------------------------|-----------|------------|
| Type                        | HP 高壓     | HVLP 環保型   |
| Fluid Output<br>出漆量 (l/Min) | 210       | 145        |
| Pattern Width<br>噴幅 (m/m)   | 270       | 300        |
| Air Cons.<br>耗氣量 (l/Min.)   | 190       | 250        |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28      |

### JS-MRP-1808 JS-MH-1808

- Optional Nozzle :  
1.3, \*1.4, 1.7, 1.9, 2.1, 2.5mm
- Cup Capacity :  
600 C.C Gravity Nylon Cup
- Gun Weight : 448 g
- Air Inlet : 1/4" PF
- Fluid Inlet : M16 X 1.5 P
- Package : 10 Pcs / Ctn / N.W. :  
10Kgs/ G..W.:11 Kgs/ 2.0'



| Item No.<br>型號              | JS-MRP1808<br>Reduced Pressure | JS-MH 1808 |
|-----------------------------|--------------------------------|------------|
| Type                        | LVMP 中壓                        | HVLP 環保型   |
| Fluid Output<br>出漆量 (l/Min) | 170                            | 145        |
| Pattern Width<br>噴幅 (m/m)   | 270                            | 270        |
| Air Cons.<br>耗氣量 (l/Min.)   | 240                            | 250        |
| Air Pressure<br>使用壓力 (PSI)  | 15~28                          | 15~28      |



## JS-G-1105

- Optional Nozzle :  
0.8,1.1,\*1.4,1.5,1.8,2.0,2.5 mm(HP)
- Cup Capacity :  
400 C.C Gravity Cup
- Gun Weight : 480 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 20 Pcs / Ctn / N.W. :  
19Kgs/ G..W.:20 Kgs/ 2.5'

| Item No.<br>型號              | JS-G1105 |
|-----------------------------|----------|
| Type                        | HP 高壓    |
| Fluid Output<br>出漆量 (l/Min) | 155      |
| Pattern Width<br>噴幅 (m/m)   | 270      |
| Air Cons.<br>耗氣量 (l/Min.)   | 200      |
| Air Pressure<br>使用壓力 (PSI)  | 30~45    |



## JS-S-1105

- Optional Nozzle :  
0.8,1.1,1.4,1.5,\*1.8,2.0,2.5 mm(HP)
- Cup Capacity :  
1000 C.C Suction Cup
- Gun Weight : 480 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 10 Pcs / Ctn / N.W. :  
19Kgs/ G..W.:20 Kgs/ 2.5'

| Item No.<br>型號              | JS-S1105 |
|-----------------------------|----------|
| Type                        | HP 高壓    |
| Fluid Output<br>出漆量 (l/Min) | 155      |
| Pattern Width<br>噴幅 (m/m)   | 270      |
| Air Cons.<br>耗氣量 (l/Min.)   | 200      |
| Air Pressure<br>使用壓力 (PSI)  | 30~45    |



## JS-G-1706

- Optional Nozzle:  
0.8 , 1.0,1.3,\*1.5 , 1.8 , 2.0 , 2.5mm
- Cup Capacity :  
400 C.C Gravity Cup
- Gun Weight : 365g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 20 Pcs / Ctn / N.W. :  
18Kgs/ G..W.:19 Kgs/ 2.5'

| Item No.<br>型號              | JS-G 1706 |
|-----------------------------|-----------|
| Type                        | HP高壓      |
| Fluid Output<br>出漆量 (l/Min) | 210       |
| Pattern Width<br>噴幅 (m/m)   | 280       |
| Air Cons.<br>耗氣量 (l/Min.)   | 220       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     |



## JS-S-1706

- Optional Nozzle :  
0.8 , 1.0,1.3,\*1.5 , 1.8 , 2.0 , 2.5 mm
- Cup Capacity :  
700 or 1000 C.C Suction Cup
- Gun Weight : 365g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" or 3/8" NPS
- Package : 10 Pcs / Ctn / N.W. :  
11Kgs/ G..W.:12Kgs/ 2.2'

| Item No.<br>型號              | JS-S 1706 |
|-----------------------------|-----------|
| Type                        | HP高壓      |
| Fluid Output<br>出漆量 (l/Min) | 190       |
| Pattern Width<br>噴幅 (m/m)   | 280       |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     |



### JS-S-1178

- Optional Nozzle :  
25W & 10W
- Cup Capacity :  
1000 C.C Suction Cup
- Gun Weight : 560 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 16MM(F)



| Item No.<br>型號              | JS-S 1178 |
|-----------------------------|-----------|
| Type                        | HP 高壓     |
| Fluid Output<br>出漆量 (l/Min) | 450       |
| Pattern Width<br>噴幅 (m/m)   | 400       |
| Air Cons.<br>耗氣量 (l/Min.)   | 230       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     |

### JS-G-1605

### JS-G-1825

- Optional Nozzle :  
1.1, \*1.4, 1.8, 2.0 mm(HP)  
1.2, \*1.4, 1.7, 2.0 mm(HVLP)
- Cup Capacity :  
400 C.C Gravity Cup
- Gun Weight : 480 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 20 Pcs / Ctn / N.W. :  
19Kgs/ G..W.:20 Kgs/ 2.5'



| Item No.<br>型號              | JS-G 1605 | JS-G 1825 |
|-----------------------------|-----------|-----------|
| Type                        | HP 高壓     | HVLP 環保型  |
| Fluid Output<br>出漆量 (l/Min) | 155       | 150       |
| Pattern Width<br>噴幅 (m/m)   | 270       | 300       |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       | 250       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28     |

### JS-M-1605

### JS-M-1825

- Optional Nozzle :  
0.8, 1.1, \*1.4, 1.5, 1.8,  
2.0, 2.5 mm(HP)  
1.2, 1.3, \*1.4, 1.7, 2.0,  
2.4 mm(HVLP)
- Cup Capacity :  
600 C.C Gravity Nylon Cup
- Gun Weight : 480 g
- Air Inlet : 1/4" PF
- Fluid Inlet : M16 X 1.5 P
- Package : 10 Pcs / Ctn / N.W. :  
10Kgs/ G..W.:11 Kgs/ 1.7'



| Item No.<br>型號              | JS-M 1605 | JS-M 1825 |
|-----------------------------|-----------|-----------|
| Type                        | HP 高壓     | HVLP 環保型  |
| Fluid Output<br>出漆量 (l/Min) | 155       | 150       |
| Pattern Width<br>噴幅 (m/m)   | 270       | 300       |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       | 250       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28     |

### JS-S-1605

### JS-S-1825

- Optional Nozzle :  
0.8, 1.1, 1.4, 1.5, \*1.8,  
2.0, 2.5 mm(HP)  
1.2, 1.3, 1.4, \*1.7, 2.0,  
2.4 mm (HVLP)
- Cup Capacity :  
1000 C.C Suction Cup
- Gun Weight : 480 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 10 Pcs / Ctn / N.W. :  
19Kgs/ G..W.:20 Kgs/ 2.5'



| Item No.<br>型號              | JS-S 1605 | JS-S 1825 |
|-----------------------------|-----------|-----------|
| Type                        | HP 高壓     | HVLP 環保型  |
| Fluid Output<br>出漆量 (l/Min) | 155       | 150       |
| Pattern Width<br>噴幅 (m/m)   | 270       | 300       |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       | 250       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28     |

## JS-S-1003 JS-SH-1003

- Optional Nozzle :  
1.0, 1.2, 1.3, \*1.4, 1.5, 1.6,  
1.8, 2.0, 2.5mm
- Cup Capacity :  
1000 C.C Alu. Suction Cup
- Gun Weight : 514 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 3/8" NPS
- Package : 10 Pcs / Ctn / N.W. :  
14Kgs/ G..W.:15 Kgs/ 1.7'



JS-KS-502



JS-KS-503



| Item No.<br>型號              | JS-S 1003 | JS-SH 1003 |
|-----------------------------|-----------|------------|
| Type                        | HP 高壓     | HVLP 環保型   |
| Fluid Output<br>出漆量 (l/Min) | 220       | 130        |
| Pattern Width<br>噴幅 (m/m)   | 310       | 300        |
| Air Cons.<br>耗氣量 (l/Min.)   | 210       | 210        |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28      |

| JS-KS 502 Airless Spray Gun                                                                                                                                                                                                                                                                                                                                                                   |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <ul style="list-style-type: none"> <li>■ MAX PRESSURE 490 BAR ( 7000 PSI )</li> <li>■ 2 Finger Trigger</li> <li>■ New Pistol grip Handle</li> <li>■ Convenient Swivel at inlet</li> <li>■ Convenient Right and Left Hand trigger Lock</li> <li>■ Nozzle : M17.5(11/16") x 16 P ,<br/>M22 (7/8") x 14 P</li> <li>■ Fluid Fitting : 1/4 BPS x 19 P , 1/4 NPS x 18P ,<br/>M 16 x 1.5P</li> </ul> |  |

| JS-KS503 Airless Spray Gun                                                                                                                                                                                                                                                                                                                                                                    |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <ul style="list-style-type: none"> <li>■ MAX PRESSURE 490 BAR ( 7000 PSI )</li> <li>■ 2 Finger Trigger</li> <li>■ New Pistol grip Handle</li> <li>■ Convenient Swivel at inlet</li> <li>■ Convenient Right and Left Hand trigger Lock</li> <li>■ Nozzle : M17.5(11/16") x 16 P ,<br/>M22 (7/8") x 14 P</li> <li>■ Fluid Fitting : 1/4 BPS x 19 P , 1/4 NPS x 18P ,<br/>M 16 x 1.5P</li> </ul> |  |

## JS-G-1006 JS-G-1106

- Optional Nozzle :  
0.8, 1.1, 1.3, \*1.4, 1.8, 2.0 mm
- Cup Capacity :  
400 C.C Gravity Cup
- Gun Weight : 315 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 20 Pcs / Ctn / N.W. :  
19Kgs/ G..W.:20 Kgs/ 2.5'



## JS-S-1006 JS-S-1106

- Optional Nozzle :  
0.8, 1.1, 1.3, 1.4, \*1.8, 2.0 mm
- Cup Capacity :  
700 or 1000 C.C Suction Cup
- Gun Weight : 315 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" or 3/8" NPS
- Package : 10 Pcs / Ctn / N.W. :  
19Kgs/ G..W.:20 Kgs/ 2.5'



| Item No.<br>型號              | JS-G 1006 | JS-G 1106 |
|-----------------------------|-----------|-----------|
| Type                        | HP 高壓     | HVLP 環保型  |
| Fluid Output<br>出漆量 (l/Min) | 175       | 170       |
| Pattern Width<br>噴幅 (m/m)   | 300       | 300       |
| Air Cons.<br>耗氣量 (l/Min.)   | 240       | 230       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28     |

| Item No.<br>型號              | JS-S 1006 | JS-S 1106 |
|-----------------------------|-----------|-----------|
| Type                        | HP 高壓     | HVLP 環保型  |
| Fluid Output<br>出漆量 (l/Min) | 150       | 140       |
| Pattern Width<br>噴幅 (m/m)   | 300       | 300       |
| Air Cons.<br>耗氣量 (l/Min.)   | 230       | 280       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     | 15~28     |





### JS-G-1888

- Optional Nozzle :  
0.8 , 1.0, 1.3, \*1.5 ,  
1.8 , 2.0, 2.5 mm
- Cup Capacity : 400 C.C Gravity Cup
- Gun Weight : 460 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 20 Pcs / Ctn / N.W. :  
20Kgs/ G..W.:21 Kgs/ 2.5'

| Item No.<br>型號              | JS-G 1888 |
|-----------------------------|-----------|
| Type                        | HP 高壓     |
| Fluid Output<br>出漆量 (l/Min) | 220       |
| Pattern Width<br>噴幅 (m/m)   | 280       |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     |



### JS-S-1888

- Optional Nozzle :  
0.8 , 1.0, 1.3, \*1.5 , 1.8 , 2.0, 2.5 mm
- Cup Capacity :  
700 or 1000 C.C Suction Cup
- Gun Weight : 460 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" or 3/8" NPS
- Package : 10 Pcs / Ctn / N.W. :  
13Kgs/ G..W.:14 Kgs/ 2.2'

| Item No.<br>型號              | JS-S 1888 |
|-----------------------------|-----------|
| Type                        | HP 高壓     |
| Fluid Output<br>出漆量 (l/Min) | 180       |
| Pattern Width<br>噴幅 (m/m)   | 280       |
| Air Cons.<br>耗氣量 (l/Min.)   | 200       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45     |



### JS-G-117

- Optional Nozzle :  
1.0, 1.3, \*1.5 , 1.8 mm
- Cup Capacity :  
400 C.C Gravity Cup
- Gun Weight : 460 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4" NPS
- Package : 20 Pcs / Ctn / N.W. :  
19Kgs/ G..W.:20 Kgs/ 2.5'

| Item No.<br>型號              | JS-G 117 |
|-----------------------------|----------|
| Type                        | HP 高壓    |
| Fluid Output<br>出漆量 (l/Min) | 200      |
| Pattern Width<br>噴幅 (m/m)   | 270      |
| Air Cons.<br>耗氣量 (l/Min.)   | 200      |
| Air Pressure<br>使用壓力 (PSI)  | 30~45    |



### JS-S-117

- Optional Nozzle :  
1.0, 1.3, \*1.5 , 1.8 mm
- Cup Capacity :  
700 or 1000 C.C Suction Cup
- Gun Weight : 460 g
- Air Inlet : 1/4" PF
- Fluid Inlet : 1/4"
- Package : 10 Pcs / Ctn / N.W. :  
11 Kgs/ G..W.:12 Kgs/ 2'

| Item No.<br>型號              | JS-S 117 |
|-----------------------------|----------|
| Type                        | HP 高壓    |
| Fluid Output<br>出漆量 (l/Min) | 185      |
| Pattern Width<br>噴幅 (m/m)   | 270      |
| Air Cons.<br>耗氣量 (l/Min.)   | 200      |
| Air Pressure<br>使用壓力 (PSI)  | 30~45    |

## JS-A15

## JS-A16

- Optional Nozzle :  
1.0, \*1.3, 2.0 mm
- Air Inlet : 1/8" PF
- Fluid Inlet : 1/8" NPS
- Gun Weight: 252g
- JS-A16 Pattern Adjustable



With compact full size automatic air-spray gun for automated painting equipment, reciprocators or robotic painting. Offering multiple mounting and spraying options.

體積小、操作反應靈敏、霧化效果卓越。JS-A16噴槍上設有噴幅寬度調整旋鈕及噴量調整旋鈕，可選擇扇形噴幅或圓錐形噴幅，噴幅寬度亦可無段調整至適當位置及任意調整噴量大小，附360度旋轉的噴槍固定座。

適用於：自動機臺模具、離型劑噴塗、塑膠冷卻、廠房消毒加濕

| Item No.<br>型號              | JS-A15 | JS-A16 |
|-----------------------------|--------|--------|
| Type                        | HP 高壓  | HP 高壓  |
| Fluid Output<br>出漆量 (l/Min) | NON    | NON    |
| Pattern Width<br>噴幅 (m/m)   | 300    | 300    |
| Air Cons.<br>耗氣量 (l/Min.)   | NON    | NON    |
| Air Pressure<br>使用壓力 (PSI)  | 30~45  | 30~45  |

## JS-A-1001

## JS-A-1002

## JS-AH-1002

- Optional Nozzle :  
0.8, \*1.0, 1.3, 1.5 mm  
(JS-A1001)
- Optional Nozzle :  
1.0, \*1.2, 1.4, 1.5, 1.6, 1.8, 2.0 mm  
(JS-A1002, JS-AH1002)
- Gun Weight : 524 g
- Air Inlet : 1/4" PF
- Fluid Inlet :: 1/4" NPS (JS-A1001) , 3/8" (JS-A1002, JS-AH2002)



With compact full size automatic air-spray gun for automated painting equipment, reciprocators or robotic painting. Offering multiple mounting and spraying options. 安裝於自動機臺。適用於皮革噴膠、冷卻等

| Item No.<br>型號              | JS-A1001 | JS-A1002 | JS-AH1002 |
|-----------------------------|----------|----------|-----------|
| Type                        | HP 高壓    | HP 高壓    | HVLP 環保型  |
| Fluid Output<br>出漆量 (l/Min) | 190      | 220      | 220       |
| Pattern Width<br>噴幅 (m/m)   | 250      | 340      | 340       |
| Air Cons.<br>耗氣量 (l/Min.)   | 270      | 270      | 290       |
| Air Pressure<br>使用壓力 (PSI)  | 30~45    | 30~45    | 15~28     |



## ■ JS K2P

2 Liter Pressure Tank

Package: 10Pcs/Ctn/N.W.:14.2Kgs/G.W.:15.2Kgs/2.7'



## ■ JS K2P + K600P

2 Liter Pressure Tank with K600P Pressure Paint Gun



### **JS-401**

#### **Dry Blow Gun**

Reduce Drying Time To Increase  
Job Through-Out

- Excellent Solution For Water-Based Applications.
- Ultra-Fine Filter Ensures Tip Quality Finish.
- Simple To Use
- 453 L/Min. ( 4 BAR )
- Weight 440 G



### ■ **JS-501S**

Dry Blow Gun Stand For 2 Dry Gun

1pc/6kgs/7kgs/0.52'



#### **HVLP Air Spary Gun**

#### **JS-S1103-250**

250C.C. Nylon Cup

#### **JS-S1103-1000**

1000C.C. Alu. Suction Cup

- Optional Nozzle :  
0.5, 0.8, 1.0, 1.3, 1.5,  
1.8, 2.0, 2.5 mm
- Air Inlet : M18x1.0P
- Fluid Inlet : 3/8" PS
- Gun Weight: 516g



### **JS-S-1212 SPRAY GUN**

- Nozzle Size: 2.5mm
- Air Inlet: 7 Bar(MAX)
- Air Pressure: 100PSI(MAX)



**1. JS-RK2**  
Stainless Steel Viscosity Cup

**2. JS-RK4**  
Nylon Viscosity Cup

**3. JS-BH02**  
1/4" Fitting

**4. JS-BH03**  
3/8" Fitting

**5. JS-NNK**  
Nozzle And Needle Are Made Of  
Stainless Steel

**6. JS-17CSET**  
17pcs Cleaning Kit

**7. JS-18CSET**  
18pcs Cleaning Kit

**8. JS-K85**  
Air Regulator

**9. Air Cap of Airless Gun**

**10. JS-PC6PF**  
Gravity Nylon Filter

**11. JS-PC27F**  
9.5m/m Suction Filter

**12. JS-PC29F**  
11.5m/m Suction Filter

**13. JS-PC29FN**  
Suction Nylon Filter

**14. JS-PC29FR**  
Suction Stainless Steel Filter

**15. JS-RDF**  
Disposable Filter

**16. JS-RDF/1**  
20pcs of JS-RDF

**17. JS-TWS**  
Water Separator

**18. JS-1112**  
Air Regulator

**19. JS-1113**  
Air Regulator

**20. JS-BH23100(10M)**

**21. JS-BH231000(100M)**

**22. JS-BH23130(130M)**  
Twin Hose 3/8"PU+Nylon Paint Hose  
Twin Hose 1/4"PU Air Hose  
Air Hose: ID 6.5m/m x OD 10m/m  
Paint Hose: ID 8.0m/m x OD 11m/m



# Accessories



JS-DPC 6AM  
600c.c Male Nylon Cup



JS-DPC 6A  
600c.c Nylon Cup



JS-1101  
125c.c Nylon Cup



JS-1106  
600c.c Aluminum  
Cup W/Alu. Lip



JS-G400S  
400c.c Stainless  
Steel Gravity Cup



JS-1107  
1000c.c Alu.  
Gravity Cup  
W/Nylon Lid  
JS-11076  
600c.c Alu.  
Gravity Cup  
W/Nylon Lid



JS-PC1-2  
Alu. 1000c.c  
Gravity Cup -1/4"  
JS-PC1-3  
Alu. 1000c.c  
Gravity Cup -3/8"



JS-PC23  
Alu. 700c.c  
Suction Cup -1/4"



JS-PC29  
Alu. 1000c.c  
Suction Cup -3/8"



無集塵/  
Non-vacuum/no vacío  
ROS-107-N5(5"/125mm)  
ROS-107-N6(6"/150mm)  
Packing: 10PCS/11.6/12.6Kg/1.7'



無集塵/  
Non-vacuum/no vacío  
ROS-N855(5"/125mm)  
ROS-N856(6"/150mm)  
ROS-N825(5"/125mm)  
ROS-N826(6"/150mm)  
Packing:10PCS/11.5/12.5KGS/1.7'



中央集塵/  
Central Vacuum/Aspiración centralizada  
ROS-107-C5(5"/125mm)  
ROS-107-C6(6"/150mm)  
Packing: 10PCS/11.6/12.6Kg/1.7'



中央集塵/  
Central Vacuum/Aspiración centralizada  
ROS-C855(5"/125mm)  
ROS-C856(6"/150mm)  
ROS-C825(5"/125mm)  
ROS-C826(6"/150mm)  
Packing:10PCS/11.5/12.5KGS/1.7'



自吸式/  
Self-Generated Vacuum/Auto vacío generado  
ROS-107-S5(5"/125mm)  
ROS-107-S6(6"/150mm)  
Packing: 6PCS/9.3/10.3Kg/2'



HOSE & BAG  
OB-46-2



自吸式/  
Self-Generated Vacuum/Auto vacío generado  
ROS-S855(5"/125mm)  
ROS-S856(6"/150mm)  
ROS-S825(5"/125mm)  
ROS-S826(6"/150mm)  
Packing:6PCS/9/10KGS/2'



HOSE & BAG  
OB-46-2

| Model NO.                | 耗氣量CFM<br>Air Cons.<br>Consumo de aire | 管徑inch(mm)<br>Hose Size<br>Tabaño de la manquera | 入氣口inch<br>Air inlet<br>La rosca de aire | 轉速RPM<br>Free Speed<br>Velocidad | 震動值m/s²<br>Vibration<br>Vibración | 噪音值dBA<br>Noise Level<br>Ruido | 偏心直徑<br>Diameter Orbit<br>Diámetro órbita | 重量Lbs./kg<br>Weight<br>Peso | 底盤尺寸inch<br>Pad Dia.<br>Plato |
|--------------------------|----------------------------------------|--------------------------------------------------|------------------------------------------|----------------------------------|-----------------------------------|--------------------------------|-------------------------------------------|-----------------------------|-------------------------------|
| N5<br>ROS-107-C5<br>S5   | 1.6                                    | 3/8(10)                                          | 1/4                                      | 11,000                           | 0.8                               | 80dBA                          | 5.0                                       | 2(0.9)                      | 5"(125)                       |
| N6<br>ROS-107-C6<br>S6   | 1.6                                    | 3/8(10)                                          | 1/4                                      | 11,000                           | 0.8                               | 80dBA                          | 5.0                                       | 2(0.9)                      | 6"(150)                       |
| N855<br>ROS-C855<br>S855 | 1.6                                    | 3/8(10)                                          | 1/4                                      | 11,000                           | 0.8                               | 80dBA                          | 5.0                                       | 2(0.9)                      | 5"(125)                       |
| N856<br>ROS-C856<br>S856 | 1.6                                    | 3/8(10)                                          | 1/4                                      | 11,000                           | 0.8                               | 80dBA                          | 5.0                                       | 2(0.9)                      | 6"(150)                       |
| N825<br>ROS-C825<br>S825 | 1.6                                    | 3/8(10)                                          | 1/4                                      | 11,000                           | 0.8                               | 80dBA                          | 2.5                                       | 2(0.9)                      | 5"(125)                       |
| N826<br>ROS-C826<br>S826 | 1.6                                    | 3/8(10)                                          | 1/4                                      | 11,000                           | 0.8                               | 80dBA                          | 2.5                                       | 2(0.9)                      | 6"(150)                       |





無集塵/  
Non-vacuum/no vacío  
**ROS-N505(5"/125mm)**  
**ROS-N506(6"/150mm)**  
**ROS-N255(5"/125mm)**  
**ROS-N256(6"/150mm)**  
Packing:10PCS/11.5/12.5KGS/1.7'



無集塵/  
Non-vacuum/no vacío  
**JS-14GH-N8(8"/200mm)**  
Packing:6PCS/12/13KGS/2'



中央集塵/  
Central Vacuum/Aspiración centralizada  
**ROS-C505(5"/125mm)**  
**ROS-C506(6"/150mm)**  
**ROS-C255(5"/125mm)**  
**ROS-C256(6"/150mm)**  
Packing:10PCS/11.5/12.5KGS/1.7'



中央集塵/  
Central Vacuum/Aspiración centralizada  
**JS-14GH-C8(8"/200mm)**  
Packing:6PCS/12/13KGS/2'



自吸式/  
Self-Generated Vacuum/Auto vacío generado  
**ROS-S505(5"/125mm)**  
**ROS-S506(6"/150mm)**  
**ROS-S255(5"/125mm)**  
**ROS-S256(6"/150mm)**  
Packing:6PCS/9/10KGS/2'



HOSE & BAG  
**OB-46-2**



自吸式/  
Self-Generated Vacuum/Auto Vacío generado  
**JS-14GH-S8(8"/200mm)**  
Packing:6PCS/12/13KGS/2'



HOSE & BAG  
**OB-46-2**

| Model NO.                | 耗氣量CFM          | 管徑inch(mm)            | 人氣口inch          | 轉速RPM      | 震動值m/s <sup>2</sup> | 噪音值dBA      | 偏心直徑            | 重量lbs/kg | 底盤尺寸inch |
|--------------------------|-----------------|-----------------------|------------------|------------|---------------------|-------------|-----------------|----------|----------|
|                          | Air Cons.       | Hose Size             | Air inlet        | Free Speed | Vibration           | Noise Level | Diameter Orbit  | Weight   | Pad Dia. |
|                          | Consumo de aire | Tabaño de la manquera | La rosca de aire | Velocidad  | Vibración           | Ruido       | Diámetro órbita | Peso     | Plato    |
| N505<br>ROS-C505<br>S505 | 1.6             | 3/8(10)               | 1/4              | 11,000     | 0.8                 | 80dBA       | 5.0             | 2(0.9)   | 5"(125)  |
| N506<br>ROS-C506<br>S506 | 1.6             | 3/8(10)               | 1/4              | 11,000     | 0.8                 | 80dBA       | 5.0             | 2(0.9)   | 6"(150)  |
| N255<br>ROS-C255<br>S255 | 1.6             | 3/8(10)               | 1/4              | 11,000     | 0.8                 | 80dBA       | 2.5             | 2(0.9)   | 5"(125)  |
| N256<br>ROS-C256<br>S256 | 1.6             | 3/8(10)               | 1/4              | 11,000     | 0.8                 | 80dBA       | 2.5             | 2(0.9)   | 6"(150)  |
| JS-14GH<br>N8/C8/S8      | 3.0             | 3/8(10)               | 1/4              | 900        | <2.5                |             | 5.0             | 3.5(1.6) | 8"(200)  |

## 2 Hand Gear-Driven Sander

Epicycloidal  
pattern of  
Gear-Driven  
Orbital Sander!



無集塵/  
Non-vacuum/no vacío  
**JS-14GH-N5(5"/125mm)**  
**JS-14GH-N6(6"/150mm)**  
Packing:6PCS/12/13KGS/2'



中央集塵/  
Central Vacuum/Aspiración centralizada  
**JS-14GH-C5(5"/125mm)**  
**JS-14GH-C6(6"/150mm)**  
Packing:6PCS/12/13KGS/2'



自吸式/  
Self-Generated Vacuum/Auto Vacío generado  
**JS-14GH-S5(5"/125mm)**  
**JS-14GH-S6(6"/150mm)**  
Packing:6PCS/12/13KGS/2'

HOSE & BAG  
OB-46-2

## Jitterbug Sanders

Pad size:75mm\*100mm for JS-SBO-813,100mm\*110mm for JS-SBO-814

HOSE & BAG  
OB-46-2



無集塵/  
Non-vacuum/no vacío  
**JS-SBO-813**  
Packing:10PCS/8.5/9.2KGS/1.2'



中央集塵/  
Central Vacuum/  
Aspiración centralizada  
**JS-SBO-813C**  
Packing:10PCS/8.5/9.2KGS/1.2'



自吸式/  
Self-Generated Vacuum/  
Auto Vacío generado  
**JS-SBO-813S**  
Packing:6PCS/7.5/8.5KGS/1.8'



無集塵/  
Non-vacuum/no vacío  
**JS-SBO-813A(Clip type)**  
Packing:10PCS/8.8/9.8KGS/1.2'



無集塵/  
Non-vacuum/no vacío  
**JS-SBO-814**  
Packing:10PCS/8.8/9.8KGS/1.2'



無集塵/  
Non-vacuum/no vacío  
**JS-SBO-814A(Clip type)**  
Packing:10PCS/8.8/9.8KGS/1.2'

## Delta Sanders

HOSE & BAG  
OB-46-2



無集塵/  
Non-vacuum/no vacío  
**JS-SBO-815**  
Packing:10PCS/8.5/9.2KGS/1.2'  
Patent: US D494,434



中央集塵/  
Central Vacuum/  
Aspiración centralizada  
**JS-SBO-815C**  
Packing:10PCS/8.5/9.2KGS/1.2'



自吸式/  
Self-Generated Vacuum/  
Auto Vacío generado  
**JS-SBO-815S**  
Packing:6PCS/7.5/8.5KGS/1.8'



| Model NO.                        | 耗氣量CFM<br>Air Cons.<br>Consumo de aire | 管 徑inch(mm)<br>Hose Size<br>Tubo de la manguera | 入氣口inch<br>Air inlet<br>La rosca de aire | 轉速RPM<br>Free Speed<br>Velocidad | 震動值m/s <sup>2</sup><br>Vibration<br>Vibración | 偏心直徑<br>Diameter Orbit<br>Diámetro órbita | 重量lbs./kg<br>Weight<br>Peso | 底盤尺寸inch<br>Pad Dia.<br>Plato |
|----------------------------------|----------------------------------------|-------------------------------------------------|------------------------------------------|----------------------------------|-----------------------------------------------|-------------------------------------------|-----------------------------|-------------------------------|
| JS-14GH<br>N5/C5/S5              | 3.0                                    | 3/8(10)                                         | 1/4                                      | 900                              | <2.5                                          | 5.0                                       | 3.3(1.5)                    | 5"(125)                       |
| JS-14GH<br>N6/C6/S6              | 3.0                                    | 3/8(10)                                         | 1/4                                      | 900                              | <2.5                                          | 5.0                                       | 3.5(1.6)                    | 6"(150)                       |
| JS-SBO<br>813/813C/<br>813S/813A | 1.6                                    | 3/8(10)                                         | 1/4                                      | 10,000                           | 0.8                                           | 3.2                                       | 1.5(0.7)                    | /                             |
| JS-SBO<br>814/814A               | 1.6                                    | 3/8(10)                                         | 1/4                                      | 10,000                           | 0.8                                           | 3.2                                       | 1.5(0.7)                    | /                             |
| JS-SBO<br>815/815C/<br>815S      | 1.6                                    | 3/8(10)                                         | 1/4                                      | 10,000                           | 0.8                                           | 3.2                                       | 1.5(0.7)                    | /                             |



# 氣動衝擊扳手 /

Air impact wrench / Llave de impacto de aire



## 1/2" Ultra & Compact JS-1084Q-FY, 1000FT/LB

Twin Hammer/Doble maza  
把手排氣 Handle Exhaust  
Exclusion del aire por el mango

10PCS/0.9cuft/G.W.:20KGS



## 1/2"Super Light Mini JS-1832T-FY, 650FT/LB

Twin Hammer/Doble maza  
把手排氣 Handle Exhaust  
Exclusion del aire por el mango

10PCS/0.9cuft/G.W.:16KGS



## 1/2"Super Light Mini JS-1584J4-FY, 1300FT/LB

Jumbo Hammer/Jumbo Maza  
把手排氣 Handle Exhaust  
Exclusion del aire por el mango

10PCS/0.9cuft/G.W.:20KGS



## 3/4"Super Light Mini JS-1584J6-FY, 1500FT/LB

Jumbo Hammer/Jumbo Maza  
把手排氣 Handle Exhaust  
Exclusion del aire por el mango

10PCS/0.9cuft/G.W.:20KGS



## 1/2" Mini Light Weight JS-1202T4-FY, 400FT/LB

Twin Hammer/Doble maza  
把手排氣 Handle Exhaust  
Exclusion del aire por el mango

10PCS/0.7cuft/G.W.:17KGS



## 3/4"Heavy Duty JS-1106-FY, 1100FT/LB

Twin Hammer/Doble maza  
把手排氣 Handle Exhaust  
Exclusion del aire por el mango

4PCS/0.85cuft/G.W.:18.6KGS



## 3/4" Light Weight JS-1464-FY, 1100FT/LB

Twin Hammer/Doble maza  
把手排氣 Handle Exhaust  
Exclusion del aire por el mango

6PCS/0.7cuft/G.W.:18KGS



| Model NO.    | 耗氣量m <sup>3</sup> /min<br>Air Cons.<br>Consumo de aire | 管徑mm<br>Hose Size<br>Tabaño de la manguera | 入氣口inch<br>Air inlet<br>La rosca de aire | 轉速RPM<br>Free Speed<br>Velocidad | 重量Kg/LB<br>Weight<br>Peso | 長度mm<br>Length<br>Longitud | 四角傳動inch<br>Square drive<br>Unidad de la plaza | 螺栓mm<br>Bolt Capacity<br>Tornillo | 最大扭力ft.lb<br>Max. torque<br>Par Maxima | 震動值m/s <sup>2</sup><br>Vibration<br>Vibración | 使用壓力PSI<br>Air pressure<br>Presion de funcionamiento |
|--------------|--------------------------------------------------------|--------------------------------------------|------------------------------------------|----------------------------------|---------------------------|----------------------------|------------------------------------------------|-----------------------------------|----------------------------------------|-----------------------------------------------|------------------------------------------------------|
| JS-1832T-FY  | 0.20                                                   | 10                                         | 1/4                                      | 12,000                           | 14(3.1)                   | 99                         | 1/2"                                           | 16                                | 650/881                                | 2.8                                           | 90                                                   |
| JS-1084Q-FY  | 0.20                                                   | 10                                         | 1/4                                      | 7,000                            | 1.8/3.96                  | 141                        | 1/2"                                           | 23                                | 1000/1356                              | 2.8                                           | 90                                                   |
| JS-1464-FY   | 0.23                                                   | 10                                         | 1/4                                      | 7,200                            | 2.6/5.7                   | 177                        | 3/4"                                           | 32                                | 1100/1491                              | 4.5                                           | 90                                                   |
| JS-1584J4-FY | 0.20                                                   | 10                                         | 1/4                                      | 9,000                            | 1.75/3.85                 | 134                        | 1/2"                                           | 25                                | 1300/1763                              | 3.1                                           | 90                                                   |
| JS-1584J6-FY | 0.20                                                   | 10                                         | 1/4                                      | 9,000                            | 1.8/3.96                  | 138                        | 3/4"                                           | 25                                | 1500/2034                              | 3.1                                           | 90                                                   |
| JS-1202-T4   | 0.20                                                   | 10                                         | 1/4                                      | 11,000                           | 1.50/3.30                 | 142                        | 1/2"                                           | 16                                | 400/542                                | 3.1                                           | 90                                                   |
| JS-1106-FY   | 0.30                                                   | 10                                         | 1/4                                      | 6,000                            | 4.15/9.13                 | 207                        | 3/4"                                           | 36                                | 1100/1491                              | 5.3                                           | 90                                                   |





Twin Hammer/Doble maza

把手排氣 Handle Exhaust  
Exclusion del aire por el mango

塑鋼氣動衝擊扳手

Composite impact wrench

Llave de impacto reversible en composite

**JS-4601**

Packing:10PCS/CTN N.W.:14.3KG G.W.:15.3 KG CUFT:0.9'



Twin Hammer

把手排氣 Handle Exhaust  
Exclusion del aire por el mango

迷你塑鋼氣動衝擊扳手

Mini Composite impact wrench

Llave de impacto reversible en composite

**JS-9701**

Packing:10PCS/CTN N.W.:14.7KG G.W.:15.7 KG CUFT:0.9'



Twin Hammer/Doble maza

把手排氣 Handle Exhaust  
Exclusion del aire por el mango

塑鋼氣動衝擊扳手

Composite impact wrench

Llave de impacto reversible en composite

**JS-5101**

Packing:10PCS/CTN N.W.:23.5KG G.W.:24.5KG CUFT:1.6'



Twin Hammer/Doble maza

把手排氣 Handle Exhaust  
Exclusion del aire por el mango

塑鋼氣動衝擊扳手

Composite impact wrench

Llave de impacto reversible en composite

**JS-7701**

Packing:6PCS/CTN N.W.:23.3KG G.W.:24.3 KG CUFT:1.3'



Twin Hammer/Doble maza

把手排氣 Handle Exhaust  
Exclusion del aire por el mango

迷你塑鋼氣動衝擊扳手

Mini Composite impact wrench

Llave de impacto reversible en composite

**JS-8701**

Packing:6PCS/CTN N.W.:23.9KG G.W.:24.9 KG CUFT:1.3'



Twin Hammer/Doble maza

Side Exhaust

氣動衝擊扳手

Air impact wrench-Extended 6"

Llave de impacto

**JS-8301**



inner trigger

| Model NO. | 耗氣量 cfm<br>Air Cons.<br>Consumo de aire | 入氣口 inch<br>Air inlet<br>La rosca de aire | 空轉轉速 RPM<br>Free Speed<br>La Velocidad | 重量 Kg/LB<br>Weight<br>Peso | 總長度 mm<br>Length<br>Longitud total | 四角傳動 inch<br>Square drive<br>Unidad de la plaza | 工作扭力 ft-lb<br>Working torque<br>Par funcional | 最大扭力 ft-lb<br>Max. torque<br>Par Maxima | 使用壓力 PSI<br>Air pressure<br>Presion de funcionamiento |
|-----------|-----------------------------------------|-------------------------------------------|----------------------------------------|----------------------------|------------------------------------|-------------------------------------------------|-----------------------------------------------|-----------------------------------------|-------------------------------------------------------|
| JS-4601   | 4.2                                     | 1/4                                       | 8,000                                  | 1.3/2.8                    | 160                                | 3/8                                             | 400ft-lb 542Nm/5s                             | 450ft-lb 610Nm/15s                      | 90                                                    |
| JS-9701   | 4.2                                     | 1/4                                       | 11,000                                 | 1.3/2.8                    | 160                                | 1/2                                             | 450ft-lb 610Nm/5s                             | 550ft-lb 745Nm/15s                      | 90                                                    |
| JS-5101   | 4.6                                     | 1/4                                       | 8,500                                  | 2.1/4.6                    | 190                                | 1/2                                             | 650ft-lb 881Nm/5s                             | 820ft-lb 1,111Nm/15s                    | 90                                                    |
| JS-7701   | 7.0                                     | 3/8                                       | 5,500                                  | 3.7/8.1                    | 220                                | 3/4                                             | 1,200ft-lb 1,627Nm/5s                         | 1,500ft-lb 2,033Nm/15s                  | 90                                                    |
| JS-8701   | 7.0                                     | 3/8                                       | 5,500                                  | 3.8/8.3                    | 230                                | 1                                               | 1,200ft-lb 1,627Nm/5s                         | 1,500ft-lb 2,033Nm/15s                  | 90                                                    |
| JS-8301   | 11.0                                    | 1/2                                       | 3,600                                  | 11.7/25.8                  | 550                                | 1                                               | 1,800ft-lb 2,440Nm/5s                         | 2,200ft-lb 2,982Nm/15s                  | 90                                                    |



**DH-7512**

Light Industry Angle Die Grinder  
20PCS/CTN 19.6/20.6 KG CUFT 1.1'



**DH-5212**

Light Industry Angle Die Grinder  
20PCS/CTN 15.6/16.6 KG CUFT 1.1



**DH-6511L**

Light Industry Die Grinder  
6PCS/CTN 9.2/10.2 KG CUFT 0.75'



**DH-7211**

Light Industry Die Grinder  
20PCS/CTN 17.4/18.4 KG CUFT 1.1'



**DH-4211**

Light Industry Die Grinder  
20PCS/CTN 14/15 KG CUFT 1.1'



**DH-5110**

Light Industry Die Grinder  
20PCS/CTN 19.6/20.6 KG CUFT 1.7'

| Model No. | Air Cons. (CFM) | Hose Size inch (mm) | Air inlet | RPM    | Collect Size inch(mm) | Weight(Lbs.(kg)) | Length inch(mm) |
|-----------|-----------------|---------------------|-----------|--------|-----------------------|------------------|-----------------|
| DH-7512   | 3.5             | 3/8                 | 1/4       | 14,000 | 1/4                   | 0.73             | 185             |
| DH-5212   | 3               | 3/8                 | 1/4       | 16,000 | 1/4                   | 0.53             | 168             |
| DH-7211   | 3.5             | 3/8                 | 1/4       | 20,000 | 1/4                   | 0.62             | 188             |
| DH-4211   | 3               | 3/8                 | 1/4       | 25,000 | 1/4                   | 0.45             | 158             |
| DH-6511L  | 3.5             | 3/8                 | 1/4       | 18,000 | 1/4                   | 1.17             | 430             |
| DH-5110   | 3               | 3/8                 | 1/4       | 22,000 | 1/4                   | 0.74             | 288             |

## 棘輪扳手 / Air Ratchet Wrench / Llave de impacto de aire



**HA-1147**

Heavy Duty Adjustable Ratchet Wrench  
20PCS/CTN 34/35 KG CUFT 1.7'



**HA-1129**

Thru-Hole Ratchet Wrench  
20PCS/CTN 17/18 KG CUFT 1.1'



**HA-1252**

Minimal Multifunction Ratchet Wrench



**HA-1251-B**

Minimal Ratchet Wrench

| Model No. | Square Drive           | Free Speed | Max.Torque       | Sound Level dB (A) | Vibration (m/s <sup>2</sup> ) | Air Pressure (PSI) | Air Inlet (NPT) | Avg. Air Cons. (CFM) | Product Length (mm) |
|-----------|------------------------|------------|------------------|--------------------|-------------------------------|--------------------|-----------------|----------------------|---------------------|
| HA-1147   | 3/8inch 1/2inch        | 160rpm     | 70 ft-lb/95 Nm   | 82                 | 5.5                           | 90                 | 1/4"            | 4                    | 275                 |
| HA-1129   | (Inner Hex) 17mm       | 400rpm     | 40 ft-lb/54 Nm   | 83                 | 3.5                           | 90                 | 1/4"            | 3                    | 227                 |
| HA-1251-B | 3/8 inch with 1/4" Hex | 300rpm     | 35 ft-lb/47.5 Nm | 83                 | 3.2                           | 90                 | 1/4"            | 3                    | 134                 |
| HA-1252   | 1/4inch (3/8 inch)     | 400rpm     | 35 ft-lb/47.5 Nm | 83                 | 3.2                           | 90                 | 1/4"            | 3                    | 159                 |

- *Ultra Fine Atomization, hinghly defined*
- *Suitable for Waterbone Paints*
- *Wide Stable Spray Pattern*
- *Perfect for the application of base and clearcoats*
- *Stainless Nozzle and Needle*
- *High Transfer Efficiency Rate > 65%*  
*Coherence HVLP 83% , LVMP 75% , LVLP 88%*  
*100 % Spray Pattern Check*

- 優質霧化技術，減少過噴，節省漆料
  - 耗風量低，使用彈性大
  - 噴幅大，型狀穩定，霧化均勻，提高生產力
  - 流線造型，符合人體工學，減少操作疲勞
  - 結構緊密堅固，持久耐用
  - 所有零件台灣生產，出廠前皆手工調校測試
  - 適用於各種溶劑型及水性漆的噴槍
  - 使用距離15～20 cm
  - 高轉換效率，高附著力
- HP 高壓大於65% ， HVLP 環保型約83% ，  
 LVMP 中壓 約75% ， LVLP 環保優型 約88%